(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 17 February 2005 (17.02.2005)

PCT

(10) International Publication Number WO 2005/014881 A2

(51) International Patent Classification⁷: C23C 18/16, 18/32, C25D 5/48

(21) International Application Number:

PCT/JP2004/011642

(22) International Filing Date: 6 August 2004 (06.08.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003-290754

8 August 2003 (08.08.2003) Л

60/566,604

30 April 2004 (30.04.2004) US


- (71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shibadaimon 1-chome, Minato-ku, Tokyo, 1058518 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KOJIMA, Tadaaki [JP/JP]; c/o Production & Technology Control Department, Gases & Chemicals Division, SHOWA DENKO

K.K., 5-1, Ogimachi, Kawasaki-ku, Kawasaki-shi, Kanagawa, 2100867 (JP). TAGUCHI, Hiroyasu [JP/JP]; c/o Production & Technology Control Department, Gases & Chemicals Division, SHOWA DENKO K.K., 5-1, Ogimachi, Kawasaki-ku, Kawasaki-shi, Kanagawa, 2100867 (JP).

- (74) Agent: SUZUKI, Shunichiro; S.SUZUKI & ASSO-CIATES, Gotanda Yamazaki Bldg. 6F, 13-6, Nishigotanda 7-chome, Shinagawa-ku, Tokyo, 1410031 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: PRODUCTION METHOD OF SUBSTRATE WITH BLACK FILM AND SUBSTRATE WITH BLACK FILM



(57) Abstract: A method for producing a substrate with black film is provided, comprising forming a dull plating film on a surface of a substrate, forming an electroless plating film containing a sulfur or nitrogen compound on the surface of the plating film, and forming a black film on the surface of the electroless plating film. This substrate with black film is used for devices which generate heat due to sliding or friction or generate/accumulate heat due to a chemical reaction, such as semiconductor device, vacuum device, rotating device and heat exchanger, and the black film has excellent heat radiating properties with an emissivity of 0.8 or more. Also, this substrate with black film has high corrosion resistance against halogen-type corrosive gases and exhibits excellent release gas properties and corrosion resistance in vacuum devices.



WO 2005/014881 A2



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

 without international search report and to be republished upon receipt of that report

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 17 February 2005 (17.02.2005)

PCT

(10) International Publication Number WO 2005/014881 A3

(51) International Patent Classification⁷: C23C 18/18, 18/32, 18/31, C25D 5/48

(21) International Application Number:

PCT/JP2004/011642

(22) International Filing Date: 6 August 2004 (06.08.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003-290754

60/566,604

8 August 2003 (08.08.2003) JP 30 April 2004 (30.04.2004) US

(71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shibadaimon 1-chome, Minato-ku, Tokyo, 1058518 (JP).


(72) Inventors; and

(75) Inventors/Applicants (for US only): KOJIMA, Tadaaki [JP/JP]; c/o Production & Technology Control Department, Gases & Chemicals Division, SHOWA DENKO K.K., 5-1, Ogimachi, Kawasaki-ku, Kawasaki-shi, Kanagawa, 2100867 (JP). TAGUCHI, Hiroyasu [JP/JP]; c/o Production & Technology Control Department, Gases & Chemicals Division, SHOWA DENKO K.K., 5-1, Ogimachi, Kawasaki-ku, Kawasaki-shi, Kanagawa, 2100867 (JP).

- (74) Agent: SUZUKI, Shunichiro; S.SUZUKI & ASSOCIATES, Gotanda Yamazaki Bldg. 6F, 13-6, Nishigotanda 7-chome, Shinagawa-ku, Tokyo, 1410031 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: PRODUCTION METHOD OF SUBSTRATE WITH BLACK FILM AND SUBSTRATE WITH BLACK FILM



(57) Abstract: A method for producing a substrate with black film is provided, comprising forming a dull plating film on a surface of a substrate, forming an electroless plating film containing a sulfur or nitrogen compound on the surface of the plating film, and forming a black film on the surface of the electroless plating film. This substrate with black film is used for devices which generate heat due to sliding or friction or generate/accumulate heat due to a chemical reaction, such as semiconductor device, vacuum device, rotating device and heat exchanger, and the black film has excellent heat radiating properties with an emissivity of 0.8 or more. Also, this substrate with black film has high corrosion resistance against halogen-type corrosive gases and exhibits excellent release gas properties and corrosion resistance in vacuum devices.

WO 2005/014881 A3



European (AT, BE, BG, CII, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report: 21 April 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.